

# ELECTROLYTIC CELL FOR THE PRODUCTION OF ALUMINIUM AND A METHOD FOR MAINTAINING A CRUST ON A SIDEWALL AND FOR RECOVERING ELECTRICITY

**Publication number:** WO0194667

**Publication date:** 2001-12-13

**Inventor:** AUNE JAN ARTHUR (NO); JOHANSEN KAI (NO); NOS PER OLAV (NO)

**Applicant:** ELKEM MATERIALS (NO); AUNE JAN ARTHUR (NO); JOHANSEN KAI (NO); NOS PER OLAV (NO)

**Classification:**

- International: C25C3/08; C25C3/00; (IPC1-7): C25C3/08

- European: C25C3/08; C25C3/08B

**Application number:** WO2001NO00221 20010529

**Priority number(s):** NO20000002889 20000607

**Also published as:**

US6811677 (B)  
US200318351  
EP1287183 (A)  
CA2411453 (A)  
CN1201034C


**Cited documents:**

US4749463  
EP0047227  
GB2076428

**Report a data error**

## Abstract of WO0194667

The present invention relates to an electrolytic cell for the production of aluminum comprising an anode and an electrolytic tank where the electrolytic tank comprises an outer shell made from steel and carbon blocks in the bottom of the tank forming the cathode of the electrolytic cells. At least a part of the sidewall of the electrolytic tank consists of one or more evaporation cooled panels, and wherein high temperature, heat resistant and heat insulating material is arranged between the evaporation cooled panels and the steel shell. The invention also includes a method for maintaining a crust on the sidewall of the tank and for recovering heat from the cooling medium inside the panel for transformation into electrical energy.



Data supplied from the esp@cenet database - Worldwide